PRODUCT INFORMATION
Penetrant testing

MR® CHEMIE
NDT-MATERIALS

MR® 79 AMS Remover

Product Characteristics

- Pre-cleaner and penetrant remover
- Fast drying
- Colourless
- Suitable for all metals and ceramics (suitability for plastics must be checked before use)
- Carrier medium Solvent
- Ketone mixture
- Leaving no residues
- Free of hydrocarbons

Minimum shelf life / Temperatures

Aerosol / Bulk:
3 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: - 30 °C - + 52 °C

Approvals / Specification

- EN ISO 3452-2
- EN ISO 3452-6
- ASTM E165
- ASTM E1417
- AMS 2644
- PMUC
- RCC-M
- ASME Code V, Art. 6
- TLV 9017 01:2011-01

Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested Products

Remover:	For all penetrant typ I, II and III; not for System “HOT”
Developer:	MR® 70, MR® 70 I (AMS), MR® 703 W (+5 °C)
Testblock:	Reference-Testblock 1and 2, ASTM Testblock

Delivery Form

technical changes reserved!

MR Chemie GmbH | Nordstr. 61-63 | 59427 Unna (Germany) | www.mr-chemie.de
Tel.: +49 (0)2303 95151-0 | Fax: +49 (0)2303 95151-10 | e-mail: post@mr-chemie.de

08.02.2022